



Aluminium AluK BSF70 Single/French Door Form

Direct Trade (Yorkshire) Ltd Unit 3 Sandall Carr Industrial Estate, Sandall Carr Road, Kirk Sandall, Doncaster, DN3 1QL.

Tel: 01302 880066 Fax: 01302 887070 Email: quotes@directtradeld.co.uk / orders@directtradeld.co.uk

Date of Order: _____ Quote Order

Reference _____ Date Required _____

Company Name _____ Delivery Address _____

Address _____

Postcode _____



Telephone _____ Fax _____ Email _____

Sign: _____ Print: _____


Overall Width (mm) _____ Overall Height (mm) _____ Open In Open Out

Including Cills & Add Ons

Single Door



French Door



Please indicate Master Door - Fingerbolt will be applied to the Slave

All viewed from the outside

Size Limitations: Each panel must be no larger than 1200mm wide & 100kg in weight, no smaller than 550mm with a Maximum height of up to 2400mm, subject to wind load deflection (No calculations made unless specified)

54mm Rebated Threshold 34mm Non Weather Rated Threshold 22mm Non Thermal Room Divider

Standard Single Colour Options:

RAL 9005 Black Matt RAL 7016 Anthracite Grey Matt RAL 9910 White High Gloss

Standard Dual Colour:

RAL 7016 Anthracite Grey Matt Externally / RAL 9910 White High Gloss Internally

RAL Internally: _____ / Colour: _____ High Gloss Semi Gloss Matt

RAL Externally: _____ / Colour: _____ High Gloss Semi Gloss Matt

Marine Guarantee Required Please Tick *For Marine Environment applications, please refer to disclaimer at foot of page.

Any of the above will incur an additional set-up cost and extended lead time

Cill: No Cill 95mm 150mm 177mm 190mm Overall Cill Size: _____ mm (Cut to Size as Standard)

Drainage: Concealed Face None

Traffic Door Handle: White Black Silver Chrome (Hinges and Associated Hardware to be Black as Standard)

Bead: Square Chamfered

28mm Glazed: Yes No (Standard 28mm glazing comprising of 4mm Tough K Softcoat + ARGON + 4mm Tough Optiwhite Swiss Black Spacer Bar)

20mm Extender 40mm Extender Trickle Vent Qty _____ (4000m² trickle vents through 40mm to the head)
Left / Right / Top Left / Right / Top

Additional Requirements:

Please Note: We cannot guarantee any product installed within 50 metres of the coast, source of pollution or 2 metres from a swimming pool against deterioration of profile or hardware. Any product fitted within 5000 metres of a hostile environment a recommended cleaning regime must be adhered to and recorded (please consult product guide) - Additional costs may be incurred, please advise on the environment if appropriate.

All frames are non-load bearing.

34mm and 22mm Low Threshold are not weather rated.

